





SG**25** SINGLE GLAZED | 38dB





HEAD CHANNEL / WALL ABUTMENT



BASE CHANNEL

Overview

Fully demountable and re-locatable single glazed system can be installed to heights of up to 3200mm using a range of glass types from 10mm to 13.5mm Toughened Laminated. SG25 has been designed for quick and easy installation offering clients a highly flexible product. The slim frame offers a nearly flush glazed solution creating exceptional aesthetics within the workplace. Frame finishes are supplied in a range of standard RAL painted finishes or can be anodised to create Brushed Stainless Steel, Polished Steel or Bright Copper and Gold finishes. A range of doors can be incorporated from fully frameless single glazed products to framed doors for better acoustics and timber solid core doors.

System Specification

Head Channel	SG1 - 25 x 25
Deflection Head Channel	SG2 - 35 x 25
Base Channel	SG3 - 23 x 25
Wall Abutment	SG1 - 25 x 25
Base Clip in	SGC - 25
Gasket	Acoustic (Clear / Black)
Toughened Glass	10mm / 12mm
Acoustic Glass	10.8mm / 12.8mm
Toughened / Laminated Glass	13.5mm
Joint Type	Clear I joint
Finish	PPC / Anodised

Acoustic Rating	up to 38dB (Rw)
Fire Rating	N/A
Line Load	up to 0.74kN p/m



SG**25**SINGLE GLAZED | **IMAGES**





