



**GLASS INTERIORS**  
INNOVATIVE GLAZING SYSTEMS

SG30 SPECIFICATION 2021 / 2022

# SG30

SINGLE GLAZED | 44dB

## Overview

Fully demountable and re-locatable single glazed system can be installed to heights of up to 3600mm using a range of glass types from 6mm to 17.5mm. Dribond30 has been designed for quick and easy installation offering clients a highly flexible product. The slim frame offers a nearly flush glazed solution creating exceptional aesthetics within the workplace. Frame finishes are supplied in a range of standard RAL painted finishes or can be anodised to create Brushed Stainless Steel, Polished Steel or Bright Copper and Gold finishes. A range of doors can be incorporated from fully frameless single glazed products to framed doors for better acoustics and timber solid core doors.

## System Specification

Head Channel	DRiSG2 - 30 x 25
Deflection Head Channel	DRiSG1 - 30 x 45
Base Channel	DRiSG3 - 30 x 25
Wall Abutment	DRiSG1 - 30 x 25
Base Clip in	DRiCF4 - 25
Gasket	Acoustic (Clear / Black)
Toughened Glass	10mm / 12mm / 15mm
Acoustic Glass	10.8mm / 12.8mm / 16.8mm
Toughened / Laminated Glass	13.5mm / 17.5mm
Joint Type	Dribond Joint
Finish	PPC / Anodised

Acoustic Rating	up to 44dB (Rw)
Fire Rating	N/A
Line Load	up to 1.5kN p/m



BASE DETAIL

HEAD DETAIL

DEFLECTION HEAD DETAIL



SG30

SINGLE GLAZED | IMAGES

